

ROLLER GRILLES & SHUTTERS • FOLDING CLOSURES • STACKDOOR

# **ECLIPSE<sup>19</sup>** 19MM ALUMINIUM ROLLER GRILLE



A heavy duty roller grille designed for shopping centres, supermarkets, carparks, and street frontage stores. It is a high-quality, durable and visually appealing architectural feature. It is designed to provide a sleek and modern look while offering functional benefits such as ventilation and protection.

SCOTTY DOORS LTD © 2023

## **19MM** ALUMINIUM ROLLER GRILLE

5

### **TECHNICAL SPECIFICATIONS**

MAXIMUM WIDTH	4000mm (Manual)   10000mm (Motorised)		
MAXIMUM HEIGHT	3000mm (Manual)   5500mm (Motorised)		
APPROX. WEIGHT PER SQM	16 kgs. per sqm		
TUBE DIAMETER	19mm		
TUBE SPACING	50mm		
BARREL TYPES	200mm spiral / 150mm steel		
BRACKETS	3mm (Manual)   6mm (Motorised)		
SIDE GUIDES	50mm/65mm deep x 50mm wide (face fixed or heal fixed)		
WIND LOCKS/TORSION BARS	YES		
DOOR FINISH	Standard Satin Silver Anodised / Dulux Duralloy Powder Coating		

#### **DOOR OPERATION**


- Manual spring-balanced operation
- Motorised operation via a single-phase or three-phase motor / controllers / limit switches, with options for external key switches, remote controls, and UPS battery back-up units

LOCKING (for Manual Operation)

• Dead Lock (keyed both sides)

#### **POWER REQUIREMENTS** (for Motorised Operation)

- Single Phase outlet (10A), located within 1 metre of the motor plug and go setup
- Three Phase 415V with neutral (10A), located within 1 metre of the motor, to be fully installed and connected by a certified electrician



#### **STANDARD DOOR SETUP**

NOTE: Manual Door Operation drawn above (for illustration purposes only).

DOOR OPERATION	HEADROOM* (mm)	SIDEROOM* (mm)	PROJECTION* (mm)
Manual spring-balanced	400	Both Sides : 120	400
Motorised (Single Phase)	550	Motor Side: 150	750





- +64 9 479 4779 | 0800 760 687 R
- office@scottydoors.com  $\boxtimes$
- www.scottydoors.com
- $\odot$ 30 Tarndale Grove, Rosedale 0632 Auckland, New Zealand

PO Box 305041, Triton Plaza 0757 Auckland, New Zealand Motorised (Three Phase)

varies

Non-Motor Side: 100

Motor Side: 300 Non-Motor Side: 120

\*minimum dimensions

750

#### **EXTERNAL WORKS BY OTHERS**

- Power supply provision, if required
- Structurally sound wall/mounting points to support the roller shutter, designed and approved by a certified engineer
- Adequate headroom, side room, and projections to ensure successful operation

#### **PRODUCT WARRANTY**

#### 12 months (Materials and Workmanship)

Scotty Doors Ltd has a continuing programme of product development and reserves the right to alter specifications at any time without notice.

A full range of extra details available at www.scottydoors.com